



*: 1- phase pump can be selected with control box (SDM) or without control box(SEM).

*: The Outlet/Connection can be made by brass/stainless steel/cast iron.

Model		Power		Max head	Max.flow	Outlet	Q (m³/h)	0	7.2	9.6	12	14.4	16.8	19.2	21.6	24	26.3
Single-phase	Three-phase	kW	HP	m	m³/h	Inch	Q (L/min)	0	120	160	200	240	280	320	360	400	440
4SDm16/3	4SD16/3	1.1	1.5	18	29	2"	 H(m)	18	16	15	14	12	11	9	8	4	3
4SDm16/4	4SD16/4	1.1	1.5	24	29	2"		24	21	20	18	15	14	12	11	6	4
4SDm16/5	4SD16/5	1.5	2	30	29	2"		30	26	25	23	19	18	14	13	8	4
4SDm16/6	4SD16/6	1.5	2	36	29	2"		36	31	30	27	23	21	17	16	9	5
4SDm16/8	4SD16/8	2.2	3	48	29	2"		48	42	39	35	33	29	23	19	14	8
4SDm16/9	4SD16/9	2.2	3	54	29	2"		54	47	44	39	37	32	26	21	16	9
	4SD16/11	3	4	64	29	2"		64	57	53	50	45	40	34	29	22	15
	4SD16/12	3	4	72	29	2"		72	65	62	55	51	44	36	30	22	16
	4SD16/14	4	5.5	87	29	2"		87	78	73	68	63	56	49	36	26	18
	4SD16/16	4	5.5	93	29	2"		93	83	77	72	65	58	54	40	29	20
	4SD16/18	5.5	7.5	109	29	2"		109	96	91	84	78	70	59	53	38	23
	4SD16/20	5.5	7.5	120	29	2"		120	109	100	94	85	76	70	55	40	26
	4SD16/22	7.5	10	133	29	2"		133	119	113	104	97	84	73	62	48	32
	4SD16/24	7.5	10	145	29	2"		145	130	123	113	105	92	80	68	52	35
	4SD16/25	7.5	10	154	29	2"		154	140	132	122	112	102	88	75	56	37